

XP-002389200

Best Available C

Best Available Copy

1/1 - (C) EPODOC / EPO  
AN - CN-97101189-A  
AP - CN19970101189 19970318  
DT - I  
EC - C04B40/00D4  
ECI - C04B40/00D4  
FAMN- 5165568  
IC - (A)  
C04B22/00  
- (C)  
C04B22/00; C04B18/08; C04B24/00  
IN - (A C)  
TANG MING [CN]; LI ZHIJIAN [CN]  
PA - (A)  
SHENYANG CONSTRUCTION ENGINEER [CN]  
- (C)  
SHENYANG BUILDING ENGINEERING [CN]  
PN - CN1193616 A 19980923  
PR - CN19970101189 19970318  
LA - en  
UNAP- 97101189  
UNIN- MING TANG; ZHIJIAN LI  
UNPA- SHENYANG CONSTRUCTION ENGINEERING COLLEGE; SHENYANG BUILDING  
ENGINEERING COLLEGE  
UNPN- CN 1193616 A  
- CN 1061328 C  
XEC - C04B-040/00D004  
XIC - C04B-022/00; C04B-040/00; C04B-018/08; C04B-024/00  
AB - (A)  
A process for preparing additives of concrete with ultrafine powdered  
coal ash includes such steps as grinding powdered coal ash its  
specific surface area is not less than 1 sq.m/g and mixing naphthalene  
water-reducing agent, wood calcium and ultrafine powdered coal ash in  
ratio of 1 : (0.2-0.5) : (8-25) to obtain pumping agent of concrete,  
or mixing naphthalene water-reducing agent with the powdered coal ash  
in ratio of 1 : (8-25) to obtain additive of high-strength concrete,  
or mixing alumina, MC, water-reducing agent and ultrafine powdered  
coal ash in ratio of 1 : (3-5) : (3-5) : (20-50) to obtain  
water-proofing agent.  
ICAI- (A C)  
C04B40/00  
ICCI- (A C)  
C04B40/00  
INW - (A C)  
TANG MING [CN]; LI ZHIJIAN [CN]  
NPR - 1  
OPD - 1997-03-18  
PAW - (A)  
SHENYANG CONSTRUCTION ENGINEER [CN]  
- (C)  
SHENYANG BUILDING ENGINEERING [CN]  
PD - 1998-09-23